SCREEN DRYING CABINETS DC-513610





Options

- · Stainless steel shelves for rustproof drying
- · Digital temperature control

HEAVY DUTY Industrial stainless steel finned heater

CAPACITY Holds up to (20) 25" x 36" (63.6 x 91.4 cm) or

up to (10) 51" x 36" (129.5 x 91.4 cm)

POWERFUL One (1) 290 CFM (8.5 CMM) air flow blower

CONSISTENT Pressurized cabin with positive air flow keeps out contaminants even if an air leak occurs

EFFECTIVE Screens sit horizontal on removable shelves (angled

to provide edge contact only)

FAST Dries fully loaded cabinet in as quickly as 40 minutes**

EFFICIENT 4" (10 cm) exhaust duct for contaminated air removal


PRECISE Light tight heavy duty double wall

EASY Simple to clean or replace filtered air intake

The VDC-513610 is capable of drying (20) 25" x 36" screens or (10) 51" x 36" screens.

10/20 Screen Drying Cabinet

The unique positionable center tree accommodate all these sizes and more!







and 47" x 31" screens.



Shown with center tree installed and 20" x 24" screens.

^{**}Drying times will vary. Humidity, thickness and type of emulsion used, and size of screens are factors in Dri-Vault curing time.



